

MAMMOTH™

S E R I E S



STOMPING THE INDUSTRY

Designed with one-piece body side construction, a curved shell, for superior strength and streamlined appearance, the New Way® Mammoth™ Front Loader comes equipped with the strongest steel specs in the industry. In addition, heavy-duty, AR450 arm skins w/ 100ksi arm bars constructed arms, torque tube assembly and Pack-on-the-Go features maximize route and labor efficiency.



GENERAL SPECIFICATIONS

| Model | 34 F | 40 F | 43 F |
|------------------------------|--------------------|--------------------|--------------------|
| Body Capacity | 22 yd ³ | 28 yd ³ | 31 yd ³ |
| Hopper Capacity | 12 yd ³ | 12 yd ³ | 12 yd ³ |
| Body Width (A) | 101.5" | 101.5" | 101.5" |
| Body Height (B) | 119.5" | 119.5" | 119.5" |
| Body Length (C) | 264" | 300" | 315" |
| Body Length Arms Down | 381" | 417" | 432" |
| Body Height Arms Down | 110.75" | 110.75" | 110.75" |
| Body Length Overall | 421" | 457" | 472" |
| *Approx. Body Weight | 16,500 lbs | 17,200 lbs | 17,400 |

MINIMUM CHASSIS SPECIFICATIONS

| Model | 34 F | 40 F | 43 F |
|-------------------|------------|------------|------------|
| Front Axle | 20,000 lbs | 20,000 lbs | 20,000 lbs |
| Rear Axle | 36,000 lbs | 44,000 lbs | 44,000 lbs |
| Total GVWR | 56,000 lbs | 64,000 lbs | 64,000 lbs |

HYDRAULIC CYLINDER SPECIFICATIONS

| Model | 34 F | 40 F | 43 F |
|-----------------------------------|------|------|------|
| Pack Cylinders 3-Stage (2) | 6.5" | 6.5" | 6.5" |
| Arm Cylinder (2) | 4.5" | 4.5" | 4.5" |
| Fork Cylinder (2) | 3.5" | 3.5" | 3.5" |
| Hopper Cover Cylinder | 2.5" | 2.5" | 2.5" |
| Tailgate Cylinder | 3" | 3" | 3" |

BODY CONSTRUCTION

| | | |
|--------------------------|-----------|-------|
| Body Sides | 1/8" | AR450 |
| Body Roof | 10 gauge | 80K |
| Body Floor | 3/16" | AR235 |
| Hopper Sides | 3/16" | AR450 |
| Hopper Floor | 1/4" | AR450 |
| Packer Plate | 3/16" | AR450 |
| Tailgate | 1/8" | AR450 |
| Forks | 1 1/4" | 100K |
| Arm Lift Capacity | 8,000 lbs | |

HYDRAULIC SYSTEMS

| | |
|--------------------------------|--------------|
| Operating Press. (6.5") | 2,450 psi |
| Pump Flow | 55 gpm |
| Oil Reservoir | 70 gal |
| Packing Force | 132,732 lbs |
| Packer Cycle Time | 25 secs. |
| Loader Arm Cycle | 13 secs. |
| Hydraulic Hoses | 4-to-1 burst |
| Return Filter | 10 micron |

STANDARD EQUIPMENT

- Air joystick control
- Front vane pump
- Auto-lock tailgate
- LED safety lights & reflectors
- Curved shell body
- Sliding hopper door
- Body side ladder
- Dual camera system
- Automatic packer
- Imron elite productive paint
- Mounting
- Pack-on-the-Go
- Air over hydraulic
- Hopper side access door
- Full ejection body
- Rear body sump with curved floor (145 gal)
- Dual sump clean out doors
- Nitrated pack cylinders

OPTIONAL EQUIPMENT

- Special lighting
- Outside controls
- 10,000 lb arm capacity
- Container disinfectant sprayer
- Pressure line filter
- Service hoist
- Electric valve
- West Coast/Lightweight model also available
- External pack cylinder hoses
- Under body valve mount

* Approximate Body Weight empty and exclusive of options. All models and specifications subject to change.

AUTHORIZED NEW WAY DISTRIBUTOR