

# WOLVERINE<sup>TM</sup>

S E R I E S



## SMALL, BUT MIGHTY

The New Way® Wolverine™ is the latest innovation from New Way Trucks and joins the largest and most diverse family of refuse products in the solid waste industry. The Wolverine has all the great features of its big brother the New Way Sidewinder™, just in a smaller package.

Although the Wolverine is a full-fledged collection vehicle, it is available in an under-CDL package, making finding and training new drivers so much easier. Your new drivers can focus on safety, customer service, and a manageable route footprint in a smaller vehicle, and eventually graduate to a full-size unit bringing those skills forward to a larger yet still familiar vehicle.

The New Way Sidewinder is the best-selling Class 8 automated side loader in the industry. It's just a matter of time before the Wolverine is the best-selling Class 6.



## GENERAL SPECIFICATIONS

Model	10W	12W	14W
<b>Body Capacity</b>	10 yd <sup>3</sup>	12 yd <sup>3</sup>	14 yd <sup>3</sup>
<b>Hopper Capacity</b>	3.3 yd <sup>3</sup>	3.3 yd <sup>3</sup>	3.3 yd <sup>3</sup>
<b>Body Width (A)</b>	96"	96"	96"
<b>Body Height (B)</b>	90.5"	90.5"	90.5"
<b>Body Length (C)</b>	160.5"	173"	183.25"

## MINIMUM CHASSIS SPECIFICATIONS

<b>* * Minimum GVWR</b>	26,000 lbs	26,000 lbs	27,500 lbs
-------------------------	------------	------------	------------

## BODY CONSTRUCTION

<b>Roof</b>	12 gauge 80K
<b>Sides</b>	12 gauge 80K
<b>Packer Ram</b>	3/16" AR450
<b>Body Floor</b>	3/16" AR235
<b>Tailgate</b>	12 gauge 80K
<b>Hopper Floor</b>	3/16" AR235
<b>Ram Guide</b>	1/4" 50K formed tracks 1/4" AR450 wear strips

## HYDRAULIC SYSTEMS

<b>Oil Reservoir</b>	46 gal
<b>Oil Flow Rate: Body</b>	30 gpm @ 1,200 rpm
<b>Oil Flow Rate: Arm</b>	30 gpm @ 1,200 rpm
<b>Body Pressure Relief</b>	3,000 psi
<b>Arm Pressure Relief</b>	3,000 psi
<b>Over Speed Protection</b>	1,500 rpm
<b>Hydraulic Tank Breather Element</b>	10 micron
<b>Hydraulic Hoses</b>	4-to-1 burst
<b>Return Line Filter</b>	10 micron absolute
<b>Suction Line Strainer</b>	100 mesh

\*\*\* Minimum Cummins L9 (or equal) engine and 3,000 series transmission required.

## PACKER SPECIFICATIONS

<b>Hopper Capacity</b>	3.3 yd <sup>3</sup>
<b>Packer Swept Volume</b>	1.1 yd <sup>3</sup>
<b>Packer Cycle Time</b>	10-12 secs.
<b>Min. Material Displacement Rate</b>	4.5 yd <sup>3</sup> /min.
<b>Packer Dimensions</b>	13" x 70"

Body construction and packer specs subject to change as product design develops.

## ARM SPECIFICATIONS

<b>Lifting Capacity at Max. Reach</b>	500 lbs
<b>Arm Cycle Time</b>	8-10 secs.
<b>Cart Capacity Able to Handle</b>	36-110 gal
<b>Arm Extension</b>	9'
<b>Min. Gripping Force</b>	1,800 psi
<b>Max. Operating Pressure</b>	2,500 psi

\* Approximate body weight empty and exclusive of options

\*\* Any chassis sent to Scranton Manufacturing with less than the minimum guideline requirements will not be mounted. (Chassis must be capable of carrying the net weight of the body plus the weight of the refuse collected.)

## STANDARD EQUIPMENT

- Multi-cycle packer
- Hopper and backup cameras
- Imron elite productive paint
- High-grade hydraulic fluid
- Smooth body sidewall design
- Fully-automatic tailgate latches
- In-cab arm & tailgate controls
- Tapered body design
- Rounded & sealed tailgate
- Double-acting tailgate cylinders
- Fully-enclosed hopper sides
- Back up & license plate lights
- Back up alarm
- Arm not stowed warning light & buzzer
- ANSI Z245.1 compliant
- Body & hydraulic 1 year warranties
- LED lights
- Electric proportional arm control
- Hopper rake teeth
- Partially covered hopper roof
- Hydraulic hopper cover

## OPTIONAL EQUIPMENT

- Available in fully and semi-automated configurations

AUTHORIZED NEW WAY DISTRIBUTOR

Sourcewell  
Formerly NJPA

Awarded Contract  
Contract # 110223-NWY

 **NEW WAY**®

800 831 1858 • [www.newwaytrucks.com](http://www.newwaytrucks.com)

PART NUMBER: 144699 23-2859 REV 12-25